


Snippets

- [Homer Dashboard Iframe Example](#)

Homer Dashboard Iframe Example

This example shows how to add a DuckDuckGo internet search to your Homer Dashboard using an iframe.



Copy this code into the config.yml file.

```
message:
  style: "is-danger"
  title: "DuckDuckGo Search Box"
  icon: "fa fa-exclamation-triangle"
  content: ' <iframe src="https://duckduckgo.com/search.html?prefill=Search
DuckDuckGo&focus=yes&kz=1&kac=1&kn=1&kp=-2&k1=-1"
style="overflow: hidden; margin: 0; padding: 0; width: calc(100% - 100px); height: 60px; "
frameborder="0"></iframe>'
```

Example config.yml

```
---
# Homepage configuration
# See https://fontawesome.com/icons for icons options

# Optional: Use external configuration file.
# Using this will ignore remaining config in this file
# externalConfig: https://example.com/server-luci/config.yml

title: "App dashboard"
subtitle: "Homer"
# documentTitle: "Welcome" # Customize the browser tab text
logo: "assets/logo.png"
# Alternatively a fa icon can be provided:
# icon: "fas fa-skull-crossbones"
```

```
header: true # Set to false to hide the header
footer: ' <p>Created with <span class="has-text-danger">♥</span> with <a
href="https://bulma.io/">bulma</a>, <a href="https://vuejs.org/">vuejs</a> & <a
href="https://fontawesome.com/">font awesome</a> // Fork me on <a
href="https://github.com/bastienwirtz/homer"><i class="fab fa-github-alt"></i></a></p>' # set
false if you want to hide it.
```

```
columns: "3" # "auto" or number (must be a factor of 12: 1, 2, 3, 4, 6, 12)
connectivityCheck: true # whether you want to display a message when the apps are not
accessible anymore (VPN disconnected for example)
```

```
# Optional theming
```

```
theme: default # 'default' or one of the themes available in 'src/assets/themes'.
```

```
# Optional custom stylesheet
```

```
# Will load custom CSS files. Especially useful for custom icon sets.
```

```
# stylesheet:
```

```
# - "assets/custom.css"
```

```
# Here is the exhaustive list of customization parameters
```

```
# However all value are optional and will fallback to default if not set.
```

```
# if you want to change only some of the colors, feel free to remove all unused key.
```

```
colors:
```

```
  light:
```

```
    highlight-primary: "#3367d6"
```

```
    highlight-secondary: "#4285f4"
```

```
    highlight-hover: "#5a95f5"
```

```
    background: "#f5f5f5"
```

```
    card-background: "ffffff"
```

```
    text: "#363636"
```

```
    text-header: "#424242"
```

```
    text-title: "#303030"
```

```
    text-subtitle: "#424242"
```

```
    card-shadow: rgba(0, 0, 0, 0.1)
```

```
    link-hover: "#363636"
```

```
    background-image: "assets/your/light/bg.png"
```

```
  dark:
```

```
    highlight-primary: "#3367d6"
```

```
    highlight-secondary: "#4285f4"
```

```
    highlight-hover: "#5a95f5"
```

```
background: "#131313"
card-background: "#2b2b2b"
text: "#eaeaea"
text-header: "#ffffff"
text-title: "#fafafa"
text-subtitle: "#f5f5f5"
card-shadow: rgba(0, 0, 0, 0.4)
link-hover: "#ffdd57"
background-image: "assets/your/dark/bg.png"
```

Optional message

message:

```
# url: "https://<my-api-endpoint>" # Can fetch information from an endpoint to override
value below.
```

```
# mapping: # allows to map fields from the remote format to the one expected by Homer
```

```
#   title: 'id' # use value from field 'id' as title
```

```
#   content: 'value' # value from field 'value' as content
```

```
# refreshInterval: 10000 # Optional: time interval to refresh message
```

```
#
```

```
# Real example using chucknorris.io for showing Chuck Norris facts as messages:
```

```
# url: https://api.chucknorris.io/jokes/random
```

```
# mapping:
```

```
#   title: 'id'
```

```
#   content: 'value'
```

```
# refreshInterval: 10000
```

```
style: "is-warning"
```

```
title: "Optional message!"
```

```
icon: "fa fa-exclamation-triangle"
```

```
content: "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
```

Optional navbar

```
# links: [] # Allows for navbar (dark mode, layout, and search) without any links
```

links:

```
- name: "Link 1"
```

```
  icon: "fab fa-github"
```

```
  url: "https://github.com/bastienwirtz/homer"
```

```
  target: "_blank" # optional html tag target attribute
```

```
- name: "link 2"
```

```
  icon: "fas fa-book"
```

```
  url: "https://github.com/bastienwirtz/homer"
```

```
# this will link to a second homer page that will load config from page2.yml and keep
```

default config values as in config.yml file

see url field and assets/page.yml used in this example:

```
- name: "Second Page"
  icon: "fas fa-file-alt"
  url: "#page2"
```

Services

First level array represents a group.

Leave only a "items" key if not using group (group name, icon & tagstyle are optional, section separation will not be displayed).

services:

```
- name: "Application"
  icon: "fas fa-code-branch"
```

A path to an image can also be provided. Note that icon take precedence if both icon and logo are set.

```
# logo: "path/to/logo"
```

items:

```
- name: "Awesome app"
  logo: "assets/tools/sample.png"
  # Alternatively a fa icon can be provided:
  # icon: "fab fa-jenkins"
  subtitle: "Bookmark example"
  tag: "app"
  url: "https://www.reddit.com/r/selfhosted/"
  target: "_blank" # optional html tag target attribute

- name: "Another one"
  logo: "assets/tools/sample2.png"
  subtitle: "Another application"
  tag: "app"
  # Optional tagstyle
  tagstyle: "is-success"
  url: "#"
```

```
- name: "Other group"
  icon: "fas fa-heartbeat"
```

items:

```
- name: "Pi-hole"
  logo: "assets/tools/sample.png"
  # subtitle: "Network-wide Ad Blocking" # optional, if no subtitle is defined, PiHole
  statistics will be shown
  tag: "other"
  url: "http://192.168.0.151/admin"
```

```
type: "PiHole" # optional, loads a specific component that provides extra features.  
MUST MATCH a file name (without file extension) available in `src/components/services`  
target: "_blank" # optional html a tag target attribute  
# class: "green" # optional custom CSS class for card, useful with custom stylesheet  
# background: red # optional color for card to set color directly without custom  
stylesheet
```